



THALIA RO2

(THALIA UNI H40 PB LONGCHAIR LEFT)

VERSIONS

THALIA R0228 (fixed)

DISTRIBUTION

CONTRACT X'clusive collection

RETAIL X'clusive collection

DESIGN

Pierre Wegnez

LABEL

Mobitec labeled product

STRUCTURE

The seat structure is made of solid beech wood with glued assemblies and stapled and glued HDF panels. To ensure optimal comfort, the armchair seat is equipped with Nosag springs.

The backrest structure is made of solid beech wood, plywood panels, and stapled and glued HDF panels. The backrest is attached to the seat with 3 M8x115 screws.

PADDING

Backrest upholstered with 3 successive layers: a layer of 55mm HD foam with a density of 55kg/m³, a layer of 20mm HR foam with a density of 35kg/m³, and a layer of 250m/m³ wadding

Seat upholstered with 3 successive layers: a layer of 50mm HR foam with a density of 43kg/m³, a layer of 30mm HT foam with a density of 45kg/m³, and a layer of 10mm HR foam with a density of 43kg/m³.

FEET

Frame made of solid beech, oak or walnut, available in various shades. Legs with round shape. Delivered with dismantled legs.

GLIDERS

Standard plastic glides, felt or metal glides on request. PTFE (Teflon) glides are also available for a supplement.

SPECIAL FEATURES

Due to the curved back, slight folds form on the inside of the backrest. The folds are controlled and provide flexibility and comfort in the back.

UPHOLSTERY

Cover	Fixed (cm)*	Loose fixed (cm)*	Loose cover (cm)*	Leather (m²)*
Uni	245	-	-	4.2
Bi**	(a) -	(a) -	(a) -	(a) -
	(b) -	(b) -	(b) -	(b) -

^{*} fabric or faux leather metres needs in cm on a roll width of 140cm, leather needs per m²

Leather and faux-leather upholsteries (always fixed)

DIMENSIONS (CM)



WEIGHT & PACKAGING

Product net weight: 21.5 Kgs Number of pieces per carton: -Carton gross weight: -Carton dimensions: -

 $[\]ensuremath{^{**}}$ The first upholstery (a) is always used for the seat.