

LOTUS C03

(LOTUS H47 PM -A)

VERSIONS

LOTUS C03 (fixed)

DISTRIBUTION

Retail/Contract Collection

DESIGN

Jana Sarlette & Pierre Wegnez

LABEL

Mobitec Label

STRUCTURE

Under press formed 10mm plywood shell

PADDING

Seat: Padded with 4 successive layers: 20mm layer Super E foam, 20mm layer of 43kg/m3 HR foam, 20mm layer of 45kg/m3 HT foam, 5mm T25 foam.

Backrest: Upholstered with 2 successive layers: 20mm layer of 43kg/m3 HR foam, 10mm layer of 35kg/m3 HR foam.

FEET

Metalfeet with epoxy finish

GLIDERS

Standard plastic gliders, felt gliders on request. For our contract customers we also offer specific glider solutions from the manufacturer Wagner.

SPECIAL FEATURES

Please note that the base frame still needs to be fitted under the seat shell after delivery. This takes about 4 minutes per chair, even for those without prior experience.

SECURITY

This product does not require any specific safety warnings, as it is safe to use under normal conditions.

UPHOLSTERY

Cover	Fixed (cm)*	Loose fixed (cm)*	Loose cover (cm)*	Leather (m²)*
Uni	110	-	-	1.7
Bi**	(a) -	(a) -	(a) -	(a) -
	(b) -	(b) -	(b) -	(b) -

* fabric or faux leather metres needs in cm on a roll width of 140cm, leather needs per m².

Leather and faux-leather upholsteries (always fixed)

** The first upholstery (a) is always used for the seat.

DIMENSIONS (CM)



88 49 55 45 55 -

WEIGHT & PACKAGING

Product net weight: 9.1 Kgs
Number of pieces per carton: 1 pc(s)
Carton gross weight: -
Carton dimensions: 68x60x50