



Metal tube structure with NOSAG springs in the seat. Injected form of a rigid

Composition of the backrest: The padding is composed of a 1st layer 20 mm HR

Frame structure made of solid beech with glued tenons and mortises.

Composition of the seat: The padding is composed of a 1st layer 20 mm HR foam (43

foam (43 kg/m3) and a 2nd layer of wadding (250 g/m2).

kg/m3) and a 2nd layer of wadding (250 g/m2).

Possible in beech, oak or solid walnut, wooden base

option, at an extra charge, PTFE/Teflon (intensive use)

plastic (for tiles, natural stone, hard floors)

MOOD 100 M01

(MOOD#100 PB10 UNI)

VERSIONS

MOOD 100 M01 (fixed)

DISTRIBUTION

CONTRACT X'clusive and RETAIL X'clusive collection

DESIGN

Vincent Dejonghe, Pierre Wegnez, Pierre-Yves Dorsimont

LABEL

MOODS labelled product

SPECIAL FEATURES

the stitching is not contrasted. The used yarn is adapted according to the chosen covering.

UPHOLSTERY

Cover	Fixed (cm)*	Loose fixed (cm)*	Loose cover (cm)*	Leather (m²)*
Uni	90	-	-	1.3
Bi**	(a) -	(a) -	(a) -	(a) -
	(b) -	(b) -	- (d)	(b) -

 * fabric or faux leather metres needs in cm on a roll width of 140cm, leather needs per m²

Leather and faux-leather upholsteries (always fixed)
** The first upholstery (a) is always used for the seat

.

SECURITY

This product does not require any specific safety warnings, as it is safe to use under normal conditions.

DIMENSIONS (CM)

felt (for parquet flooring) metal (for carpets)

STRUCTURE

PADDING

FEET

GLIDERS

polyurethane foam



WEIGHT & PACKAGING

Product net weight: 7.4 Kgs Number of pieces per carton: 2 pc(s) Carton gross weight: 17.9 Kgs Carton dimensions: -

mobitec